





LLOYD INSTRUMENTS™

An AMETEK Company



Materials Testing
Solutions 1 kN - 300 kN
225 lbf - 67443 lbf

About Us

Lloyd Instruments is a world-leading manufacturer of innovative materials testing systems offering customers a wide choice of machine models suitable for testing the physical and mechanical properties of any material, component or product.

Lloyd Instruments is a business unit of AMETEK Test & Calibration Instruments Division. Both are part of AMETEK, Inc., a global manufacturer of electronic instruments and electromechanical devices with over 60 manufacturing plants around the world. AMETEK has been a NYSE listed company since 1930 (symbol: AME).

www.ametek.com

Lloyd Instruments offers expert materials test solutions for all types of applications. All of our machines can perform tests such as:

Tensile Strength	Compression
Flexure/Bend Strength	Coefficient of Friction
Puncture Strength	Tear Resistance
Peel Strength	Shear Strength
Delamination Strength	Bond Strength
Adhesion Strength	Break Load
Creep and Stress Relaxation	Crush Resistance
Deformation Strength	Ductility
Elastic Limit	Elongation
Rupture Strength	Young's Modulus
Toughness	Torsion



Contents

Materials Testing Solutions	3	Materials Testing Applications	10
Systems and Accessories	4	- Plastics	
- High Elongation Sample Testing		- Products and Components	
- Large Sample Testing		- Packaging	
- Grips and Fixtures		- Adhesive Tapes	
- Extensometers		- Rubber	
- Safety		- Metals	
- Elevated and Low Temperature Testing		- Textiles	
NEXYGENPlus Materials Testing Software	6	- Foams	
- Test Creation		- Paper and Board	
- Data Collection		- Food	
- Reporting and Exporting Test Data		Technical Specifications	14
- Video and Still Picture Capture		Software Demonstration CD	flap
- Test Data Security and Audit Trails		Davenport Plastics & Polymer Testing Instruments	back page
- Test Automation and Customisation			



Materials Testing Solutions

1 kN 225 lbf	5 kN 1124 lbf	10 kN 2248 lbf	20 kN 4496 lbf	30 kN 6744 lbf	50 kN 11241 lbf	100 kN 22481 lbf	150 kN 33722 lbf	300 kN 67443 lbf
-----------------	------------------	-------------------	-------------------	-------------------	--------------------	---------------------	---------------------	---------------------

Lloyd Instruments *Plus* Series of materials testing machines are the culmination of 40 years experience in materials testing. These high performance machines, available in single or twin column design, enable you to make accurate and repeatable force measurements in the range from 0.1 N to 300 kN (0.0225 lbf - 67443 lbf). Depending on the machine, elongations of between 1 micron and 2.5 m (98.4 in) can be measured.

Lloyd Instruments materials testing solutions allow our customers to:

- Develop world-class products through extensive product development testing
- Cost effectively manufacture products to the highest quality
- Demonstrate the superior performance of their products
- Ensure their product is manufactured in conformance with international or industry standards
- Verify their supplier specifications
- Provide traceable test results

The Markets We Serve

Lloyd Instruments *Plus* Series of materials testing machines are suitable for use in quality control, production, laboratory, R&D or education. The application range is extensive with the following markets commonly served:

Plastics	Packaging
Automotive	Medical
Pharmaceutical	Metals
Paper and Board	Wood
Textiles	Electronics
Building Materials	Products and Components

World Class Manufacturing

By partnering with a company operating in a Six Sigma environment, our customers can be assured of complete satisfaction through high quality products and services. Lloyd Instruments Six Sigma programmes enable us to provide complete materials testing solutions by understanding our customers' aims and objectives.

Worldwide Support

Our global network of service and support is available to provide you with applications assistance, training, service and accredited calibrations. Please see our web site for details of your nearest support office.

Achievements

Visit our web site for details of solutions we have provided to many well-known global companies.

www.lloyd-instruments.com

Accreditations

- ISO 9001:2000
- ISO TickIt accredited materials testing software
- UKAS accredited force calibration laboratory
- Accredited to ISO 17025 for calibration



CERTIFICATE No GB98/11777



0251

Single and Twin Column Test Machines

Robust, high stiffness load frames are at the core of each materials testing system. Configuring a system could not be easier. Simply choose a suitable machine load frame, load cell, grip for holding the sample, optional materials testing software and accessories such as an extensometer.

Advanced electronics ensures accurate data collection exceeding the requirements of BS EN 7500-1 and ASTM E4.


Key Features:

- 8 kHz data sampling rate to capture all data points
- Accurate load rate control and load holding
- Console stores 10 test set-ups and 600 test results
- Multi-lingual and multi-unit display options
- Intelligent plug and play load cells and accessories
- Automatic diagnostics and load cell calibration check
- Comprehensive warranty
- Fast delivery times


Load System Compliance Compensation

Our advanced frame design and load chain compliance (or stiffness) compensation means extension errors of less than 5 microns at full load are achievable for many compression and flexural tests without the use of an extensometer.

The graphs show the load chain deflection for a typical machine system (left) and a Lloyd Instruments compensated system (right).



Typical system stiffness



Lloyd Instruments system stiffness



High Elongation Sample Testing

Extended height frames are available for all single and twin column systems for testing samples up to 2.5 m (98.4 in) high depending on the model used. Reduced height versions are also available for short travel tests where space is limited.




Large Sample Testing

Our unique pogo system is compatible with all bench mounted single and twin column machines. This allows testing of very large samples up to 2 x 2 m (78.7 x 78.7 in) in size with the added benefit of optional elevated and low temperature testing capability.



Grips and Fixtures

Choose from a wide range of standard grips and fixtures as well as custom designed versions.



- Wedge action grips for rigid samples
- Pneumatic action grips for faster sample clamping
- Vice action grips for films and semi rigid materials
- Compression platens available in many sizes
- 3 and 4 point bending jigs
- Self tightening grips to reduce operator fatigue
- Bollard grips for wire and rope testing

[See our online grips data sheets for more information](#)

Extensometers

Plug and play extensometers are designed for accurate measurement of elongation and determination of results such as modulus, yield and proof stress amongst others.

- Contacting strain gauge type for rigid materials
- Automatic contacting long travel type for rubbers and elastomers
- Non-contacting laser type for high elongations



Laser extensometer



Clip-on extensometer



Safety

All machines conform to CE and other international regulations. Hardware and software overload detection, both in test mode and jog mode, can be configured independently.

Fitting an optional interlocked safety shield enhances operator safety. Shields can be integrated into the test procedure by using our NEXYGENPlus materials testing software, allowing tests to start automatically once the door is closed.

Elevated and Low Temperature Testing

Thermal chambers and furnaces are offered by Lloyd Instruments for testing from -70°C to +1200°C.

Chambers and furnaces can be optionally controlled by NEXYGENPlus software.



NEXYGENPlus multi-lingual materials testing software is the hub of any Lloyd Instruments materials testing system.


This extraordinarily easy to use and flexible software, allows the operator to control and monitor all aspects of the system from a single intuitive user interface.

This ensures fast, reliable and powerful testing in addition to fingertip control of data analysis features.

NEXYGENPlus is supplied as a complete all-inclusive package with no additional modules required. The package includes:

- Complete standards library
- Complete suite of test set-ups
- Video and still picture capture system
- Security and audit trail utility
- SPC trend and histogram charts
- User interface customisation facility
- Data export utility for connection to LIMS and SPC packages

▶ *Play the enclosed demonstration CD to see these powerful software features in action.*



'Welcome' screen


► *Play the enclosed demonstration CD to see these powerful software features in action.*

Test Creation


Getting started with NEXYGEN*Plus* could not be simpler thanks to the extensive built-in library of test methods covering ASTM, DIN, EN, ISO and

other standards. Unlike similar systems, we supply our complete standards library to all customers, in addition to complete test wizards for tension, compression, tearing, peeling, friction and flexural tests.

The standard User Configurable Test can be used to create specialist multi-stage tests and is particularly beneficial for product and component testing.



Standards library



Standard test set-ups


Data Collection

NEXYGEN*Plus* is configured to allow rapid and accurate data collection with many built-in functions to ensure error free testing.


When measuring sample dimensions, operators will save time and avoid data entry errors by using the standard functionality for direct reading of digital callipers and micrometers.

Ensuring that operators use the correct fixtures and load cell is a common issue in materials testing. NEXYGEN*Plus* features the ability to create help screens that can include pictures for operator guidance in addition to restricting test operation to a particular value load cell.

Clear pass/fail indications are displayed when the test is complete. Supervisors can also be alerted automatically to any failures by an e-mail that includes a copy of the test data.



Customisable pre-test user help screen




Facility to enter sample identification data

Reporting and Exporting Test Data

NEXYGENPlus software features many flexible data analysis tools allowing you to quickly analyse the captured data.

Built in SPC functionality enables continuous monitoring of process parameters such as C_p and C_{pk} .



SPC chart




Video capture is particularly useful when testing products and components

Video and Still Picture Capture

Whether for advanced sample failure analysis or presentation of test results, video and stills capture is a feature unique to NEXYGENPlus.

Entire tests can be videoed and synchronised with the stress/strain data and replayed for detailed post-test analysis.

Microsoft® Office integration allows seamless transfer of data to familiar Windows® packages such as Word and Excel® for further analysis. You can also export data to your favourite LIMS, SPC or data management systems by using our versatile data export facility.



Still picture capture system

Alternatively, still images can be taken at specific points during the test. These still images are recorded on the graph for easy analysis.

To utilise these powerful features, simply connect your web cam or analogue video camera to your PC.


▶ *Play the enclosed demonstration CD to see these powerful software features in action.*

Test Data Security and Audit Trails


The NEXYGEN*Plus* security and audit trail module enables supervisors to manage user access and data traceability. The module can also be configured to assist manufacturers with FDA 21 CFR Part 11 compliance requirements.

Electronic signatures and the ability to restrict user access rights increase security and avoid costly errors.

Integrated audit trails covering operator usage and test results guarantee that all changes to test procedures are recorded in a simple retrievable format.



Configuration of user access rights



Automated sample handling system

Test Automation and Customisation

To facilitate the increasing use of automation in manufacturing, NEXYGEN*Plus* has been developed with powerful utilities for systems integration. Typical integration projects include, automated sample handling, in-line testing and the monitoring of parameters from additional measurement systems such as thermocouples and strain gauges.

NEXYGEN*Plus* can be configured to suit your exact operational requirements.

Quick and easy customisation of the user interface and other functionality can be achieved via the integrated Microsoft® VBA module.





A single machine can be used for a vast number of applications.

The following section details common applications and key international standards by industry sector.

Plastics

The testing of raw materials requires highly accurate and repeatable data to allow preparation of material data sheets. A wide range of grips is available, including pneumatic grips for reducing operator fatigue and constant pressure gripping.

Our extensometers enable our customers to accurately measure parameters such as modulus, yield strength and elongation to failure. For flexural and compression tests, Lloyd Instruments machines can compensate for load frame and fixture deflection ensuring highly accurate data acquisition.



Test Type	Standard / Application
Tensile strength, elongation to break, yield strength, modulus, Poisson's ratio	ASTM D638, ASTM D1708, ASTM D2990, ASTM D3291, ASTM D3807, ASTM D3846, ASTM D3914, ASTM D4321, ASTM D4475, ASTM D4476, ISO 527, BS 2782, DIN 53504
Compression	ASTM D695, ASTM D2412, ISO 604, BS 2782
Flexural	ASTM D790, ISO 178, BS 2782
Shear	ASTM D732
Friction	ASTM D1894

For details of our Davenport™ equipment for measuring melt index, HDT/VICAT, density and falling dart impact properties of plastic films, please see the back cover.

Products and Components



The testing of many products and components often requires test methods that are not based on international standards.



NEXYGEN^{Plus} software can be configured for any multi-stage test method that is required. Configurable user access rights and audit trails benefit customers working in the medical device or pharmaceutical industries.

Markets served include:

Medical device, automotive, pipes, building materials, electronics, aerospace, packaging, defence and many more.



Dedicated FTPlus friction tester

Packaging


The testing of packaging requires an extremely versatile materials testing system due to the varying requirements within industries such as pharmaceutical, cosmetics, food and beverages. A single system from Lloyd Instruments will allow you to test in compliance with all standards shown below and many more.

Test Type	Standard / Application
Tensile strength, elongation, yield strength	ASTM D882, ISO 527
Static and kinetic coefficients of friction	ASTM D1894, ISO 8295
Tearing strength	ASTM D1004, ASTM D1938, ISO 6383
90° and 180° peeling of heat bonded seals	Seal Strength
Puncture resistance	ASTM D5748, EN 14477
Cardboard compression, flexure, ECT, BCT, FCT, SCT	ISO 5628, ISO 3037, ISO 12048, EN 23035, ISO 9895

Adhesive Tapes


Lloyd Instruments 1 kN (225 lbf) LFPlus materials testing system can be configured to test in accordance with the FINAT methods below.

Test Type	Standard / Application
180° peel	FTM1
90° peel	FTM2
Low speed release	FTM3
Loop tack	FTM9
Dynamic shear	FTM18



Rubber

The testing of rubber materials commonly requires machines capable of measuring very high strain in addition to testing at temperatures above and below ambient.



Lloyd Instruments offers extended column machines ideal for rubber applications that are compatible with long travel contacting and non-contacting extensometers.

Thermal chambers for testing between -70°C and +300°C are also available for the study of material properties at temperatures other than ambient.



Standard test methods within NEXYGENPlus software include:

Test Type	Standard / Application
Tensile	ISO 37, ASTM D412, ASTM D413, ASTM D429, ASTM D4482
Tear	ASTM D624

Metals



The key to accurate metals testing to international standards is the ability to measure the stress and strain to a very high degree of accuracy.

For metals testing, Lloyd Instruments offers a wide range of extensometers to measure such parameters as Young's modulus and proof stress.

Furnaces for testing metals up to 1200°C are also available. Standard test methods within NEXYGENPlus software allow simple and fast test creation to international standards such as:

Test Type	Standard / Application
Tensile	EN 10002, EN ISO 8496, ISO 6892, ASTM E8, ASTM A370
N value	ISO 10275
Bending	ASTM E290, ASTM E1012, EN 13523, EN ISO 7438, EN ISO 8491
Erichsen cupping test	DIN 50101



Floor mounted LR100KPlus 100 kN (22481 lbf) test machine


Textiles

The Lloyd Instruments *Plus* Series capability covers the testing of a wide range of textile products including:

Geo-textiles	Knitted products	Ropes
Fibre and yarn	Thermal insulation	Nets
Coated textiles	Non-wovens	Webbing

Test types include:

Seam slippage	Tensile strength
Compressive strength	Puncture resistance
Tear resistance	Trouser tear



Test Type	Standard / Application
Tensile textiles	ASTM D1682, EN ISO 13934, ASTM D1578, EN ISO 13934, EN ISO 13935, EN 29073, EN ISO 2062
Tensile geo-textiles	ASTM D4884, ASTM D4632, ASTM D4595, EN ISO 10319, EN ISO 10321

Foams

Several compression/relaxation tests can be performed on foam samples, measuring the forces at various percentages of compression to international standards such as ASTM D3574.


Test Type	Standard / Application
Compression	ASTM D3574, ISO 3386, BS 4098
Tensile	ASTM D3574



Paper and Board

Tests such as Z direction fibre strength, bending, friction and compressibility can be easily performed using NEXYGEN*Plus* software. Data from all tests can be combined into a single material properties data sheet.

Test Type	Standard / Application
Tensile wet & dry	EN 1607, EN 1608, ASTM C203
Flexural	EN 12089, ASTM C446, ASTM C203
Compression	EN 826, ASTM C165, EN 1605, EN 12089
Friction	TAPPI



Food

Lloyd Instruments also supplies a dedicated food texture analyser featuring all the benefits of the *Plus* Series machines and NEXYGEN*Plus* software.

Please contact Lloyd Instruments for further details.

Texture analysers are used to measure properties including:

TPA	Consistency	Gumminess
Adhesiveness	Crispness	Hardness
Chewiness	Firmness	Springiness
Cohesiveness	Gel strength	Stickiness

Our application knowledge and expertise is immense. If you don't see your application here, please contact us.


Technical Specification

Single Column Machines

Model	LFPlus	LRXPlus	LR5KPlus
Force Capacity	1 kN (225 lbf)	5 kN (1124 lbf)	5 kN (1124 lbf)
Force Capacity - Extended Machine Version	1 kN (225 lbf)	2.5 kN (562 lbf)	5 kN (1124 lbf)
Maximum Crosshead Travel (<i>Between Eye Ends</i>)	500 mm (19.7 in)	735 mm (29 in)	975 mm (38.4 in)
Maximum Crosshead Travel - Extended Machine Version (<i>Between Eye Ends</i>)	750 mm (29.5 in)	1370 mm (54 in)	1463 mm (57.6 in)
Crosshead Speed Range	0.05 to 1270 mm/min (0.002 to 50 in/min) at full load	0.01 to 1016 mm/min (0.0004 to 40 in/min) at full load	0.01 to 1016 mm/min (0.0004 to 40 in/min) at full load
Maximum Return Speed	1270 mm/min (50 in/min)	1016 mm/min (40 in/min)	1016 mm/min (40 in/min)
Speed Accuracy	< 0.2% at steady state	< 0.2% at steady state	< 0.2% at steady state
Minimum Load Resolution (<i>Load Cell Specific</i>)	0.0001 N	0.0001 N	0.0001 N
Load Cell Accuracy	< 0.5%	< 0.5%	< 0.5%
Extension Resolution	< 2 microns	< 0.1 microns	< 0.1 microns
Data Sampling Rate	8 kHz	8 kHz	8 kHz
Extensometer Inputs	Digital and Analogue	Digital and Analogue	Digital and Analogue
Load Measuring System	EN ISO 7500: 2004 Class 0.5 ASTM E4	EN ISO 7500: 2004 Class 0.5 ASTM E4	EN ISO 7500: 2004 Class 0.5 ASTM E4
A Width Between Columns (<i>Daylight</i>)	N/A	N/A	404 mm (16 in)
B Machine Height	923 mm (36 in)	1260 mm (49.6 in)	1555 mm (61.2 in)
B Machine Height - Extended Machine Version	1173 mm (46 in)	1995 mm (78.5 in)	2055 mm (80.9 in)
C Machine Width (<i>with Console</i>)	500 mm (19.7 in)	564 mm (22.2 in)	820 mm (32.3 in)
D Machine Depth	400 mm (15.7 in)	400 mm (15.7 in)	480 mm (18.9 in)
E Throat Depth	179 mm (7 in)	135 mm (5.3 in)	N/A
Weight	46 kg (102 lb)	50 kg (110 lb)	99 kg (218 lb)
Weight - Extended Machine Version	48 kg (106 lb)	52 kg (115 lb)	103 kg (227 lb)
Humidity	5 - 85% RH (Non-condensing)	5 - 85% RH (Non-condensing)	5 - 85% RH (Non-condensing)
Operating Temperature	5 to 35°C (41 to 95°F)	5 to 35°C (41 to 95°F)	5 to 35°C (41 to 95°F)
Storage Temperature	-20 to 55°C (-4 to 131°F)	-20 to 55°C (-4 to 131°F)	-20 to 55°C (-4 to 131°F)
Supply Voltage	230Vac ±10% 50-60 Hz Fuse T1AH250V 115Vac ±10% 50-60 Hz Fuse T2AH250V	230Vac ±10% 50-60 Hz Fuse T3.15AH250V 115Vac ±10% 50-60 Hz Fuse T6.3AH250V	230Vac ±10% 50-60 Hz Fuse T3.15AH250V 115Vac ±10% 50-60 Hz Fuse T6.3AH250V
Maximum Power Requirement	120VA max	500VA max	500VA max

* Includes same electronics as used in all Plus Series machines

Single Column Machines




Twin Column Machines


Bench Mounted Machines

LR10KPlus	EZ20 (Plus*)	LR30KPlus	EZ50 (Plus*)	LR50KPlus	LS100Plus
10 kN (2248 lbf) 10 kN (2248 lbf) 950 mm (37.4 in) 1435 mm (56.5 in)	20 kN (4496 lbf) 20 kN (4496 lbf) 870 mm (34.3 in) 1370 mm (54 in)	30 kN (6744 lbf) 30 kN (6744 lbf) 870 mm (34.3 in) 1370 mm (54 in)	50 kN (11241 lbf) 50 kN (11241 lbf) 855 mm (33.7 in) 1355 mm (53.4 in)	50 kN (11241 lbf) 50 kN (11241 lbf) 855 mm (33.7 in) 1355 mm (53.4 in)	100 kN (22481 lbf) 100 kN (22481 lbf) 824 mm (32.4 in) 1012 mm (39.8 in)
0.01 to 508 mm/min (0.0004 to 20 in/min) at full load	0.001 to 508 mm/min (0.00004 to 20 in/min) at full load 0.01 to 1016 mm/min (0.0004 to 40 in/min) at half load	0.001 to 508 mm/min (0.00004 to 20 in/min) at full load	0.01 to 254 mm/min (0.0004 to 10 in/min) at full load	0.001 to 508 mm/min (0.00004 to 20 in/min) at full load	0.001 to 254 mm/min (0.00004 to 10 in/min) 0 to 50 kN 0.001 to 101.6 mm/min (0.00004 to 4 in/min) 50 to 100 kN
508 mm/min (20 in/min) < 0.2% at steady state 0.0001 N	1016 mm/min (40 in/min) < 0.2% at steady state 0.0001 N	508 mm/min (20 in/min) < 0.2% at steady state 0.0001 N	254 mm/min (10 in/min) < 0.2% at steady state 0.0001 N	508 mm/min (20 in/min) < 0.2% at steady state 0.0001 N	254 mm/min (10 in/min) < 0.2% at steady state 0.0001 N
< 0.5% < 0.05 microns 8 kHz	< 0.5% < 0.1 microns 8 kHz	< 0.5% < 0.05 microns 8 kHz	< 0.5% < 0.03 microns 8 kHz	< 0.5% < 0.05 microns 8 kHz	< 0.5% < 0.03 microns 8 kHz
Digital and Analogue EN ISO 7500: 2004 Class 0.5 ASTM E4	Digital and Analogue EN ISO 7500: 2004 Class 0.5 ASTM E4	Digital and Analogue EN ISO 7500: 2004 Class 0.5 ASTM E4	Digital and Analogue EN ISO 7500: 2004 Class 0.5 ASTM E4	Digital and Analogue EN ISO 7500: 2004 Class 0.5 ASTM E4	Digital and Analogue EN ISO 7500: 2004 Class 0.5 ASTM E4
404 mm (16 in) 1555 mm (61.2 in) 2055 mm (80.9 in) 820 mm (32.3 in) 480 mm (18.9 in)	404 mm (16 in) 1567 mm (61.7 in) 2067 mm (81.4 in) 868 mm (34.2 in) 596 mm (23.5 in)	404 mm (16 in) 1567 mm (61.7 in) 2067mm (81.4 in) 868 mm (34.2 in) 596 mm (23.5 in)	404 mm (16 in) 1567 mm (61.7 in) 2067 mm (81.4 in) 868 mm (34.2 in) 596 mm (23.5 in)	404 mm (16 in) 1567 mm (61.7 in) 2307 mm (90.8 in) 868 mm (34.2 in) 596 mm (23.5 in)	404 mm (16 in) 1567 mm (61.7 in) 1857 mm (73.1 in) 868 mm (34.2 in) 596 mm (23.5 in)
N/A	N/A	N/A	N/A	N/A	N/A
99 kg (218 lb) 103 kg (227 lb) 5 - 85% RH (Non-condensing) 5 to 35°C (41 to 95°F) -20 to 55°C (-4 to 131°F)	148 kg (326 lb) 152 kg (335 lb) 5 - 85% RH (Non-condensing) 5 to 35°C (41 to 95°F) -20 to 55°C (-4 to 131°F)	148 kg (326 lb) 152 kg (335 lb) 5 - 85% RH (Non-condensing) 5 to 35°C (41 to 95°F) -20 to 55°C (-4 to 131°F)	148 kg (326 lb) 152 kg (335 lb) 5 - 85% RH (Non-condensing) 5 to 35°C (41 to 95°F) -20 to 55°C (-4 to 131°F)	148 kg (326 lb) 152 kg (335 lb) 5 - 85% RH (Non-condensing) 5 to 35°C (41 to 95°F) -20 to 55°C (-4 to 131°F)	200 kg (441 lb) 204 kg (450 lb) 5 - 85% RH (Non-condensing) 5 to 35°C (41 to 95°F) -20 to 55°C (-4 to 131°F)
230Vac ±10% 50-60 Hz Fuse T3.15AH250V 115Vac ±10% 50-60 Hz Fuse T6.3AH250V 500VA max	230Vac ±10% 50-60 Hz Fuse T5AH250V 115Vac ±10% 50-60 Hz Fuse T10AH250V < 1000VA	230Vac ±10% 50-60 Hz Fuse T5AH250V 115Vac ±10% 50-60 Hz Fuse T10AH250V < 1000VA	230Vac ±10% 50-60 Hz Fuse T5AH250V 115Vac ±10% 50-60 Hz Fuse T10AH250V < 1000VA	230Vac ±10% 50-60 Hz Fuse T5AH250V 115Vac ±10% 50-60 Hz Fuse T10AH250V < 1000VA	230Vac ±10% 50-60 Hz Fuse T5AH250V 115Vac ±10% 50-60 Hz Fuse T10AH250V < 1000VA

Twin Column Bench Mounted Machines



Twin Column Floor Standing Machines



Floor Standing Machines


LR100KPlus	LR150KPlus	LR300K
100 kN (22481 lbf)	150 kN (33722 lbf)	300 kN (67443 lbf)
100 kN (22481 lbf)	150 kN (33722 lbf)	N/A
1150 mm (45.3 in)	1150 mm (45.3 in)	1295 mm (51 in)
1620 mm (63.8 in)	1620 mm (63.8 in)	N/A
0.001 to 508 mm/min (0.00004 to 20 in/min) at full load	0.001 to 254 mm/min (0.00004 to 10 in/min) at full load	0.01 to 254 mm/min (0.0004 to 10 in/min) at full load
508 mm/min (20 in/min)	254 mm/min (10 in/min)	254 mm/min (10 in/min)
< 0.2% at steady state	< 0.2% at steady state	< 0.2% at steady state
0.0001 N	0.0001 N	0.0001 N
< 0.5%	< 0.5%	< 0.5%
< 0.05 microns	< 0.04 microns	< 0.03 microns
8 kHz	8 kHz	100 Hz
Digital and Analogue	Digital and Analogue	Analogue
EN ISO 7500: 2004	EN ISO 7500: 2004	EN ISO 7500: 2004
Class 0.5 ASTM E4	Class 0.5 ASTM E4	Class 0.5 ASTM E4
620 mm (24.4 in)	620 mm (24.4 in)	620 mm (24.4 in)
2471 mm (97.3 in)	2471 mm (97.3 in)	2674 mm (105.3 in)
2970 mm (116.9 in)	2970 mm (116.9 in)	N/A
1509 mm (59.4 in)	1509 mm (59.4 in)	1509 mm (59.4 in)
733 mm (29.9 in)	733 mm (29.9 in)	733 mm (29.9 in)
N/A	N/A	N/A
900 kg (1984 lb)	900 kg (1984 lb)	1200 kg (2647 lb)
910 kg (2006 lb)	910 kg (2006 lb)	N/A
5 - 85% RH	5 - 85% RH	5 - 85% RH
(Non-condensing)	(Non-condensing)	(Non-condensing)
5 to 35°C	5 to 35°C	5 to 35°C
(41 to 95°F)	(41 to 95°F)	(41 to 95°F)
-20 to 55°C	-20 to 55°C	-20 to 55°C
(-4 to 131°F)	(-4 to 131°F)	(-4 to 131°F)
230Vac ±10%	230Vac ±10%	3 phase
50-60 Hz	50-60 Hz	
Fuse T5AH250V	Fuse T5AH250V	
115Vac ±10%	115Vac ±10	
50-60 Hz	50-60 Hz	
Fuse T10AH250V	Fuse T10AH250V	
< 1000VA	< 1000VA	< 2000VA



An AMETEK Company

This document contains many AMETEK trademarks and registered trademarks, including, but not limited to, the AMETEK mark and logo. All other company, product and service marks, logos, or images are copyrighted trademarks or service marks of their respective owners.

Materials Testing Solutions for any Application



NEXYGEN™
PLUS



LLOYD 
INSTRUMENTS



AMETEK®
TEST & CALIBRATION INSTRUMENTS

Demonstration CD
NEXYGEN*Plus* Materials Testing Software

www.lloyd-instruments.com

All rights of the producer of the software reserved.
Unauthorised copying strictly prohibited.
© by AMETEK, Inc.

Davenport™ Plastics & Polymer Testing Instruments

To complement our range of materials testing systems, Lloyd Instruments also offers the complete solution for polymer and plastics testing applications, from raw material to finished product.



Our established range of Davenport polymer test instruments, specified in many international testing standards, allows critical polymer parameters to be determined, including melt flow index (MFI), melt flow rate (MFR), melt volume rate (MVR), melt density/viscosity, intrinsic viscosity (IV) and melt viscosity (MV) of PET, impact strength of plastic film, density measurement, HDT and VICAT and coefficient of friction measurements.

Instruments include:

- Melt Flow Indexers (meets ISO 1133, ASTM D1238 Methods A & B)
- Melt Viscometers (PET testing)



- HDT/VICAT Instruments (Temperature Deflection of Thermoplastic Materials) (meets VICAT: EN ISO 306, ASTM D1525-98 1/10, BS 2782 Part 1: Method 120C 1990 and HDT: EN ISO 75-1 and 75-2, ASTM D648-98C)
- Density Measuring Columns (meets ASTM D1505, ISO 1183, BS 2782 Part 6: Method 620D)
- Falling Dart Impact Testers (meets EN ISO 7765-1:2004, ASTM D1709 Methods A & B)
- Inclined Plane Friction Testers



www.ametek.com

UK

Lloyd Instruments Ltd
12 Barnes Wallis Road
Segensworth East, Fareham
Hants, PO15 5TT

Tel +44 (0)1489 486 399
Fax +44 (0)1489 885 118
E-mail uk-far.general@ametek.co.uk
Web www.lloyd-instruments.co.uk

USA

AMETEK Test & Calibration Instruments - Americas
Harriman Business Center
1220 Washington Avenue
Building 7A, Suite 300
Albany, New York 12226

Tel +1 (518) 689 0222
Fax +1 (518) 689 0225
E-mail TCI.sales@ametek.com
Web www.lloyd-instruments.com

Far East

AMETEK Singapore Pte Ltd
10 Ang Mo Kio Street 65
#05-12 Techpoint
SINGAPORE 569059

Tel +65 6484 2388
Fax +65 6481 6588
E-mail aspl@ametek.com.sg
Web www.lloyd-instruments.com

AMETEK, Inc.
Shanghai Representative Office
Rm 912, Metro Tower
30 Tian Yao Qiao Road
Shanghai 200030
China

Tel +86 21 6426 8111
Fax +86 21 6426 7818 Ext 12
E-mail lloyd@ametek.com.cn
Web www.lloyd-instruments.com

France

AMETEK S.A.S.
Rond Point de l'Épine des Champs
Buro Plus - Bât. D
78990 Elancourt

Tel +33 (0)1 30 68 89 40
Fax +33 (0)1 30 68 89 49
E-mail general.lloyd-instruments@ametek.fr
Web www.lloyd-instruments.fr

Germany

AMETEK GmbH
Rudolf-Diesel-Straße 16
D-40670 Meerbusch

Tel +49 (0)2159 9136-0
Fax +49 (0)2159 9136-39
E-mail info@ametek.de
Web www.ametek.de

© 2007, by AMETEK, Inc. All rights reserved.
Specifications subject to change without notice.

P-MT-6000-0107
January 2007



CERTIFICATE No GB98/11777



0251